

## Barcode Printer

# XP-470B

## Create For You



### Product close up



Streamlined Industrial Design.



USB 2.0 Interface, High Speed Printer.

XP -470B is professional thermal direct label printer produced by Xprinter.

High performance and professional printing various type of labels ,small and affordable .

Direct thermal label printer your best choice.

High Speed



High Quality



High performance




### Product Features

- High quality double-walled clamshell design
- 203 dpi and 300 dpi resolution models
- Head-up sensor
- USB 2.0
- 8MB SDRAM, 4 MB Flash

### Application

- Express logistics industry
- Small office or home office mailings
- Shelf labeling
- Healthcare specimen labeling
- File-folder labeling
- Inventory and asset management

# Direct Thermal Barcode Printer



Printer model	XP-470B
Resolution	8 dots/mm(203 DPI)
Printing method	Direct Thermal
Max. print speed	127 mm (5")/S
Max. print width	108 mm (4.25")
Max. print length	2286 mm (90")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	20-112mm (0.78"-4.4")
Media thickness	0.06 ~ 0.16 mm (2.36 ~ 6.3 mil)
Label length	10 ~ 2,286 mm (0.4" ~ 90")
Label roll capacity	127 mm (5") OD (outside wound)
Enclosure	Double-walled plastic
Physical dimension	240 mm (W) x 211 mm (H) x 166 mm (D)
Weight	2.15kg
Processor	32-bit RISC CPU
Memory	4MB Flash Memory
	8MB SDRAM
	SD card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0
Power	External universal switching power supply
	Input: AC 100-240V, 2.5A, 50-60Hz
	Output: DC 24V, 2.5A, 60W
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: red, purple & blue)
Sensors	Black mark reflective sensor (position adjustable)
	Head open sensor
	Transmissive gap sensor
Internal fonts	8 alpha-numeric bitmap fonts
	Windows fonts are downloadable from software.
Barcode	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
	2D bar code: PDF-417, Maxicode, DataMatrix, QR code
Font and barcode rotation	0°、90°、180°、270°
Printer language	TSPL(EPL、ZPL、DPL)
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing
	Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC、CE、CCC、CB
Environmental concern	RoHS
Accessories	①Windows labeling software, driver and user manual CD ②quick start guide ③USB cable ④power cord ⑤external switching power adapter ⑥label spindle, fixing tab x 2
Factory options	① Real time clock ② Peel-off module
User options	① external roll mount (1"core) ② external roll mount board



Scan QR code to check out Xprinter website for more update information.

